

## 10 LOW HEADROOM HOIST ND, REEVING: 04

### Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P5/T5 motor		F gear + P5/T5 motor		H gear + P6/T6 motor		J gear + P7/T7 motor	
		High	Low	High	Low	High	Low	High	Low
6300	3m/M6	4	0,7	5	0,8	8	1,3	10	1,7
8000	3m/M6	4	0,7	5	0,8	8	1,3	10	1,7
10000	2m/M5	4	0,7	5	0,8	8	1,3	10	1,7

### Hoist dimensions

HOL m	Length code	M1 mm	H2 mm	H3 mm	L12 mm	W mm	Weight kg
9	D	697	88	569	1058	708	610
12	E	817	118	689	1178	828	660
16	F	967	156	839	1328	978	710

### Motor dimensions

Motor	P5	P6	P7	T5	T6	T7
M2 (mm)	728	722	762	728	722	722
Weight (kg)	58	85	105	45	65	71

### Trolley dimensions

B min.	B max.	D1 (Ø)	D2 (Ø)	H1							
100	610	125	63	314							
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	
175	489	620	654	3	40	35	262	60	513	106	

D002117\_A  
004991

### C-dimensions

B	C
100 - 199	610
200 - 289	575
290 - 430	530
431 - 530	595
531 - 610	650

Note: Weight calculated with P5 motor.

Note: All dimensions in mm.

