

## 11 LOW HEADROOM HOIST ND, REEVING: 04, EXTENDED LOAD

### Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P5/T5 motor		F gear + P5/T5 motor		H gear + P6/T5 motor		J gear + P7/T7 motor	
		High	Low	High	Low	High	Low	High	Low
12500	1Am/M4	4	0,7	-	-	-	-	-	-

### Hoist dimensions

HOL m	Length code	M1 mm	H2 mm	H3 mm	L12 mm	W mm	Weight kg
9	D	697	88	569	1058	708	610
12	E	817	118	689	1178	828	660
16	F	967	156	839	1328	978	710

### Motor dimensions

Motor	P5	P6	P7	T5	T6	T7
M2 (mm)	728	722	762	728	722	722
Weight ( kg)	58	85	105	45	65	71

### Trolley dimensions

B min.	B max.	D1 (Ø)	D2 (Ø)	H1							
100	610	150	63	313							
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	
175	488	619	653	4	44	48	272	47	510	107	

D002118\_A  
005000

### C-dimensions

B	C
100 - 199	655
200 - 289	620
290 - 430	585
431 - 530	650
531 - 610	695

Note: Weight calculated with P5 motor.  
Note: All dimensions in mm.

