

8 LOW HEADROOM HOIST NC, REEVING: 04

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P2/T2 motor		F gear + P2/T2 motor		H gear + P4/T4 motor	
		High	Low	High	Low	High	Low
2500	3m/M6	4	0,7	5	0,8	8	1,3
3200	2m/M5	4	0,7	5	0,8	8	1,3

Hoist dimensions

HOL m	Length code	M1 mm	H3 mm	H2 mm	L17 mm	W mm	Weight kg
11	C	567	474	73	792	505	335
15	D	667	574	99	892	605	355

Motor dimensions

Motor	P2	P4	T2	T4
M2 (mm)	567	690	507	610
Weight (kg)	35	53	22	45

Trolley dimensions

B min.	B max.	D1 (Ø)	D2 (Ø)	H1							
100	490	63	100	175							
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
122	161	318	535	554	38	3	45	240	42	427	746
L13	L14	L15	L16								
647	551	49	52								

D002107_A
062529

C-dimensions

B	C
100 - 240	340
241 - 300	380
301 - 350	415
351 - 400	445
401 - 450	480
451 - 490	510

Note: Weight calculated with P2 motor.

Note: All dimensions in mm.

