

19 DOUBLE GIRDER HOIST ND, REEVING: 04

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P5/T5 motor		F gear + P5/T5 motor		H gear + P6/T6 motor		J gear + P7/T7 motor	
		High	Low	High	Low	High	Low	High	Low
6300	3m/M6	4	0,7	5	0,8	8	1,3	10	1,7
8000	3m/M6	4	0,7	5	0,8	8	1,3	10	1,7
10000	2m/M5	4	0,7	5	0,8	8	1,3	10	1,7
12500	1Am/M4	4	0,7	-	-	-	-	-	-

Hoist dimensions

HOL m	Length code	M1 mm	M2 mm	H1 mm	H2 mm	Min R mm	Weight kg
9	D	697	259	640	88	1400	670
12	E	817	259	640	118	1400	700
16	F	967	372	753	156	1700	745
20	G	1157	522	903	201	2000	785

Motor dimensions

Motor	P5	P6	P7	T5	T6	T7
M3 (mm)	728	722	762	728	722	722
Weight (kg)	58	85	105	45	65	71

Trolley dimensions

C1	C2	D1 (Ø)	D2 (Ø)	D3 (Ø)	WB	WW min	WW max				
421	477	110	140	63	1000	50	75				
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
470	382	400	15	98	1296	420	100	500	500	648	648
L13	L14	L15	L16	L17							
148	88	900	148	255							

D002119_A
005021

Note: Weight calculated with P5 motor.

Note: All dimensions in mm.

Note: Min R with service platform and second brake.

Note: Standard rail gauges: 1400, 1700 and 2000.

