

79 NORMAL HEADROOM HOIST ND, REEVING: 02

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P5/T5 motor		F gear + P5/T5 motor		H gear + P6/T6 motor		J gear + P7/T7 motor	
		High	Low	High	Low	High	Low	High	Low
4000	3m/M6	8	1,3	10	1,7	16	2,7	20	3,3
5000	2m/M5	8	1,3	10	1,7	16	2,7	20	3,3
6300	1Am/M4	8	1,3	-	-	-	-	-	-

Hoist dimensions

HOL m	Length code	M1 mm	M3 mm	H2 mm	Weight kg
18	D	697	494	176	750
24	E	817	494	235	820
32	F	967	522	309	900
40	G	1157	522	403	960

Motor dimensions

Motor	P5	P6	P7	T5	T6	T7
M2 (mm)	728	722	762	728	722	722
Weight (kg)	58	85	105	45	65	71

Trolley dimensions

B min	B max	C	D1 (Ø)	D2 (Ø)	H1						
120	610	1080	63	100	301						
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
1000	253	161	60	1028	259	195	35	412	28	68	4
L13	L14	L15	L16	L17	L18	L19					
40	40	150	697	513	671	601					

D002114_A
062272

Note: Weight calculated with P6 motor, when B=300mm.

Note: All dimensions in mm.

